







Supacat

J8 Light Patrol Vehicle

Vehicle Specification

ing	jine	
n	Petrol	Turbo

2.0 Petrot rurbo

2.0 Petrol Turbo Hybrid

3.0 V6 Turbo Diesel

272 bhp = 62.5 kW/tonne 400 Nm = 200 Nm/litre

272 bhp + 17.3 kWh = 87.5 kW/tonne

637 Nm = 318 Nm/litre 260 bhp = 59.4 kW/tonne

650 Nm = 200 Nm/litre

760 mm

Fuel tank capacity 70-81 litres

Fuel tank driving range 700-850 km

Maximum speed 177 km/h

Transmission type 8 speed automatic
Low ratio 3.73:1

Low ratio 3.73:1

Vehicle dimensions 4850mm (L) x 1877mm (W) x 1995mm (H)

Weight (GVW) 3200 kg

Payload (minimum - Can be extended) 1000 kg

Towing weight-braked 2495 kg

Ground clearance 237 mm

Wheelbase 3008 mm

Approach angle 41°

Departure angle 35°

Turning circle 5.9 m

Features

360° turret ring
Jerry can holder
Optional seats
Floor protection

Fording depth (with no modifications)

Up to .50 cal and ammo storage 4 x 20 litres or 8 x 5.56 cal ammo boxes Tactical seats with ballistic protection options LINE-X® protective coating